



**The EU Framework Programme for Research and Innovation H2020
Research and Innovation Action**

CENTAURO

Deliverable 8.4 Final CENTAURO System Evaluation

Dissemination Level: Public

Project acronym:	CENTAURO
Project full title:	Robust Mobility and Dexterous Manipulation in Disaster Response by Fullbody Telepresence in a Centaur-like Robot
Grant agreement no.:	644839
Lead beneficiary:	KHG – Kerntechnische Hilfsdienst GmbH
Authors:	Uwe Süß, Michael Gustmann, Michael Felsberg, Tobias Klamt
Work package:	WP8 – Requirement Specification & Evaluation
Date of preparation:	2018-11-15
Type:	Report
Version number:	1.0

Document History

Version	Date	Author	Description
0.1	2018-11-06	Uwe Süß	Initial draft
0.2	2018-11-15	Tobias Klamt	Review
1.0			Submitted version

Executive Summary

This deliverable summarizes the results of the CENTAURO final system evaluation based on the system requirements formulated in Task T8.1. According to the Grant Agreement, the Final System Evaluation in Task T8.3 is the last stage of the evaluation campaign and part of milestone MS4.

During this evaluation, the CENTAURO system has performed a set of complex disaster-response tasks, benchmarking many of the system's capabilities. The tasks have been designed following special rules inspired by the ELROB 2018 (European Land Robot Trial). The results have been analysed and assessed with respect to predefined performance levels.

The overall result of this evaluation was very positive. The vast majority of the tasks could be solved completely. Almost all of the remaining tasks were partly solved. The final evaluation has shown that the CENTAURO system complies to a large extent with the specified functionality.

Contents

1	Introduction	5
2	Evaluation Planning	6
3	Execution of the Evaluation	9
4	Evaluation Results	18
5	Analysis	20
6	Conclusions	21
	Annex A: Evaluation Protocol	22
	Annex B: Evaluation tasks	23
	Annex C Protocols	30

1 Introduction

Following the project plan, the integrated CENTAURO system with full functionality was evaluated in final test scenarios at the end of the project. These scenarios were defined in task T8.1 and are based on disaster-response benchmark scenarios and inspired by robot competitions and challenges, such as RoboCupRescue, the DARPA Robotics Challenge (DRC), the DLR SpaceBot Cup, and the European Land Robot Trial (ELROB). Input from professional rescue workers like our end user KHG has been used to ensure the relevance of the different tasks.

The KHG site outside Karlsruhe was chosen as the location for the evaluation tasks, given that its existing infrastructure provides an optimal base for these tests. All available data was captured and analyzed to obtain a final evaluation of the system and give an assessment of its capabilities.

This deliverable contains a documentation of the final system evaluation.

2 Evaluation Planning

Before the evaluation was carried out, the rules, the test methodologies, the rating, and the different tasks for the CENTAURO system were defined.

2.1 Rules

The rules of the final evaluation test of the CENTAURO system were inspired by the ELROB 2018 (European Land Robot Trial).

2.1.1 Definition of Staff Roles

The staff involved in the evaluation was organized in:

- operating crew,
- operators,
- person at location (PAL), and
- referee.

The *operating crew* prepared the robot. During the starting procedure of the CENTAURO system, all crew members were allowed to work on it.

Two members of the operating crew acted as *operators* (main operator and support operator). As soon as the system was ready, they gave a “ready” signal this to the referee and as soon as they received the “starting” signal, they started with the task execution. During execution, the operators were not allowed to get in contact with other crew members.

The *PAL* was member of the operating crew and accompanied the robot during a task. In normal mode, no communication between the operators, the operating crew and the PAL was allowed. In the case of an operational problem and with the consent of the referee, the operators were allowed to contact the PAL who could potentially interact with the robot. In case of an emergency, the PAL could interrupt the operation (emergency stop).

The *referee* was not member of the operating crew. He was responsible to define the operation start and communicate this “start signal” to the operators. In addition, he rated and recorded the success on task fulfillment and supervised the compliance with the rules. In case of an emergency, he could also interrupt the operation (emergency stop).

2.1.2 Operation Modes

There were two operation modes defined:

- Tele-operated robot operation and
- Supervised autonomous robot operation.

In *tele-operated mode*, the operators were allowed to control the robot at any time during the trial.

In *supervised autonomous mode*, the robot operated autonomously while supervised by the operators. Direct control was only allowed to provide the robot with necessary input data before the robot starts operation and to receive result data from the robot after the trial finished. During the tests, the operators were allowed to monitor the system. However, for safety reasons, the operators were always able to stop autonomous execution and to take over control of the system.

2.1.3 Test Procedure

To start a test, the scenario and the robot had to be set up. As soon as the robot was in the defined starting configuration and all required hardware and software systems on the robot side

as well as on the operator side were started, the main operator gave the “ready signal” to the referee. As soon as the “start signal” was given by the referee, task execution was started. The operators had no direct visual contact to the robot or its workspace at any time during the procedure.

Data connection between the operator station and the robot was realized by either cable or wireless data link. Robot power supply was either given by cable or an internal battery. With respect to the high costs of some robot components, the robot was secured by a support structure composed of a mobile suspension and a chain block during some of the tests.

2.1.4 Evaluation Measurements

Test protocols were conceived to document the test and analyze the evaluation results after execution. They contain arrays to specify the task e.g., the number of trials, the starting parameters, the test target and the achieved results.

In addition, the start and end time of the test and the operation time were recorded for each trial. The operation time is defined to be the time from the start of the task until the task is finished with either “success”, “partial success” or “no success”.

The referee rated each task by assigning a performance level. The 100 %-criterion was defined in the task description. Every interaction between the PAL and the robot, the PAL and the operators, or the referee and the robot had a negative influence on the performance measure. In case of an emergency stop, the performance level was 0 %.

Protocols for all tasks are attached in Annex A.

2.2 Evaluation Tasks

Testing arenas developed by NIST and RoboCupRescue offer a valuable testbed to evaluate the CENTAURO system. Certain test cases (tasks) were first specified in CENTAURO Deliverable D8.1 and then further defined at the CENTAURO consortium meeting at IIT, Genoa in September 2018.

These tasks were classified in the categories

- Locomotion,
- Manipulation,
- Autonomy, and
- Combined.

As a final task an

- Integrated Mission

was specified after the evaluation of the single tasks.

2.2.1 Locomotion Tasks

- L2 Step field: Move the robot over an uneven field with debris.
- L3 Stair: Walk up a flight of stairs.
- L4 Gap: Overcome a gap.

2.2.2 Manipulation Tasks

- M2 Fire hose: Connect a fire hose to a nozzle using a tool.
- M3 230V-connector: Connect a standard 230 Volt and a CEE-type connector.
- M4 Shackle: Attach a shackle to a handle
- M5 Screw driver: Screw a wooden board to a wooden block.
- M6 Driller: Drill holes at defined positions into a wooden block with a two-handed driller.

2.2.3 Autonomous Tasks

- A1 Autonomous locomotion: Hybrid driving-stepping navigation over challenging terrain.
- A2 Autonomous manipulation: Autonomous dual arm grasping of a power tool.

2.2.4 Combined Tasks

- L1 Regular door with handle and lock: Unlock and open the door away from the robot.
Move the robot through it.
- M1 Valve: Approach the workspace by climbing a platform, open, and close a gate type and a lever type valve.
- M7 Pipe star: Grasp and view different parts of a pipe star.

2.2.5 Integrated Mission

- IM1 Integrated Mission: Multiple locomotion and manipulations tasks queued to a mission which covers many aspects of a disaster-response mission.

3 Execution of the Evaluation

To perform the different tasks, either the Full-body telepresence stations (see Figure 1), the support operator control interfaces (see Figure 2), or a combination of both was used to control the robot. The support operators interface included several subsystems such as a joystick, a keyframe editor, a semi-autonomous stepping controller, or a 6D mouse. The two tasks “Autonomous manipulation” and “Autonomous locomotion” were performed in the autonomous mode without direct control but under supervision of the operators.



Figure 1: The Full-body Telepresence suit.



Figure 2: Control interfaces of the support operators.

3.1 Task L1: Regular door

The robot started 100 cm in front of the door (H x W: 200 cm x 90 cm) which it was approach and open (see Figure 3). An adaptor for standard keys special tool (which is often used by KHG in disaster response tasks) was to be used to unlock the door with two rotations of the key (see Figure 4). The robot was to push down the door handle and open the door away from its body with its second. Finally, the robot was to move through the door.




Figure 3: CENTAURO approaching the door with the key adapter in its left hand.



Figure 4: Detail view on the key adapter.

3.2 Task L2: Step field

A step field of size $L \times W = 240 \times 140$ cm with a maximal height difference of 20 cm was randomly generated out of concrete blocks. The step field itself followed a grid structure with 20 cm edge length. Five wooden beams were randomly placed on the field as debris. The robot started 100 cm in front of the step field and was to overcome it, as shown in Figure 5.



Figure 5: Centauro overcoming the step field.

3.3 Task L3: Stair

A stair case was built out of concrete blocks. It was 120 cm wide and was composed of three steps of 20 cm height and 30 cm depth. The topmost stair ended in a platform, as shown in Figure 6. The robot started 100 cm in front of this stair case and was to climb it to reach the goal pose on the platform.



Figure 6: Stair case.

3.4 Task L4: Gap

Two platforms of 140 cm width and 120 cm length with a 50 cm gap between them were composed out of concrete blocks. The robot started on the one platform and was to overcome the gap to reach the goal pose on the other platform. Figure 7 depicts the task.



Figure 7: Centauro in the start configuration of the gap task.

3.5 Task M1 Valves (gate type; lever type)

Two valves of gate type (8 cm diameter) and lever type were mounted on a wall at 120 cm height. A platform of size $W \times L \times H = 140 \times 60 \times 20$ cm was positioned in front of the valves on the ground. The robot was to start 100 cm in front of the platform. It was to climb the platform with its front feet to obtain a suitable manipulation pose, as shown in Figure 8. It was then to open and close both valves.




Figure 8: Centauro climbing the platform with its front feet to obtain a suitable manipulation pose for the valves.

3.6 Task M2: Fire hose

A nozzle was mounted in a height of 100 cm. The robot started 100 cm in front of the nozzle with a fire hose in his one hand and a corresponding tool in the other hand. The robot was to approach the nozzle, connect the fire hose to the nozzle, and use the tool to fasten it (Figure 9).



Figure 9: Centauro using a special tool to fasten the fire hose to the nozzle.

3.7 Task M3: 230 Volt Connector

In the first subtask, a standard household 230 V connector had to be plugged in a cable-outlet. The robot started with the plug in his right hand. The outlet was hanging from the ceiling, positioned in a reachable position in front of the robot. Figure 10 left shows Centauro performing this subtask.

In the second subtask, the robot had to plug a CEE-Type 230 V connector into an outlet, mounted at the wall in a height of 100 cm. The robot was to open the lid with his one hand before inserting the plug which was positioned in his other hand, as shown in Figure 10 right.




Figure 10: Centauro performing the plug task. Left: Standard 230 V household plug. Right: CEE-Type 230 V plug.

3.8 Task M4: Fixation of a shackle

A metal ring was mounted at a wall in a height of 100 cm. The robot started in a distance of 100 cm with a shackle in its left hand and the corresponding screw, mounted to a grasping adapter, in its other hand. The robot was to approach the workspace fix the shackle to the ring which required to turn the screw by five rotations. The task execution is depicted in Figure 11.




Figure 11: Centauro fixing a shackle to a metal ring.

3.9 Task M5: Screw driver

A wooden board with two pre-mounted screws was to be screwed to a wooden block at the wall in a height of about 100 cm. The robot started in 100 cm distance to the wall with the wooden board in left hand and an electrical screwdriver in his right hand. It was to position the board, and subsequently screw the screws which also included triggering the tool. Figure 12 shows Centauro during screwing.



Figure 12: Centauro screwing a screw to fix a wooden board to a wooden block.

3.10 Task M6: Driller

The robot was to drill three holes at defined positions in a wooden block at a height of 100 cm. In the start configuration, the robot already carried the two-handed driller in its hands and was positioned 100 cm away from the wooden block. Figure 13 shows how the driller tip approaches the wooden block.



Figure 13: Centauro approaching the wooden block with the driller tip.

3.11 Task M7: Pipe star

A “pipe star” (see Figure 14) which is a standard test object for the evaluation of disaster response platforms was placed on the ground. The robot was to approach the object and inspect each of the five pipes by touching it in a certain orientation and provide the operators a view in the inside of each pipe where a symbol – a so called Landoltring – was to be observed. The latter subtask was to be solved by moving on of the robot cameras to a suitable position.




Figure 14: The used pipe star.

3.12 Task A1: Autonomous locomotion

The robot started 200 cm in front of a field of gravel and several obstacles. A flight of stairs, consisting of two steps and ending in a platform was positioned in some distance behind the gravel. First, the operator was to define a goal pose on the platform. The robot was then to plan two path alternatives to the operator. The operator was to choose one of these alternatives with the robot finally was to execute. Figure 15 shows how Centauro climbed stairs to reach the final goal pose after gravel was surrounded by omnidirectional driving.




Figure 15: Centauro autonomously climbing stairs after navigating around gravel.

3.13 Task A2: Autonomous manipulation

A two-handed driller was placed on a table. The robot started directly in front of this table (see Figure 16). It was to autonomously grasp the driller, trigger it, lift it and move it around.



Figure 16: Centauro in front of the two-handed driller which it was to grasp autonomously.

3.14 Task IM1: Integrated mission

The integrated mission comprised multiple selected tasks. It was specified after the evaluation of the single tasks.

To provide a maximum of flexibility and to come as close to a realistic setup as possible, it was planned to perform the IM1

- with power supply by battery,
- with data connection by WiFi, and
- without crane and safety structure.

The robot was to start on the KHG courtyard in a distance to the building of about 30 m with a radiation measurement device in its hands. It was then to approach the building where it would find a radiation source to measure and read out the measurement device screen output through a robot camera. After dropping the device, the robot was to open one of the electric garage doors by pressing the corresponding button. Consequently, it was to enter the building and open an unlocked door with a handle. Subsequently, the robot was to grasp a mobile overview camera attached to a buoy and pull this through the door into the next room where it was to be positioned at a location that provides good overview.

In the new room the robot was to find a lever type valve with a 20 cm high platform in front which was blocked by a hand lift truck. The robot was to pull this lift truck away from the workspace, climb the platform with its front feet and turn the valve. Next, it was to leave the platform and disconnect an electrical plug. In another part of the room, the robot was to approach a table on which it was to find an electrical screw driver. It was to grasp this screw driver and use it to unscrew a wooden board which blocks the robot's way. To avoid the wooden board from falling down, the robot was to grasp it with its other hand before unscrewing and place it at a suitable place after unscrewing.

Finally, the robot was to leave the building through the now traversable passage and through another garage door and climb a flight of stairs with three steps which ends in a platform. A van was parked next to this platform leaving a gap of about 30 cm. The robot was to overcome this gap to enter the trunk of the van which was the goal position of this mission.

4 Evaluation Results

During the CENTAURO Final Evaluation test 17 tasks were performed. Eleven tasks have been carried out with complete success, two tasks were almost complete, three tasks have been performed with partial success, and one task failed (Table 1).

Table 1: Results of the Final Evaluation.

Nr.	Task name	Task object	Performance level			
			100%	99 - 90%	89 - 1%	0%
1	L1	Regular door with handle and lock	X			
2	L2	Step-field with debris	X			
3	L3	Stair	X			
4	L4	Gap	X			
5	M1	Valve (gate type)			X (60%)	
7		Valve (lever type)	X			
8	M2	Fire hose	X			
9	M3	230 V Connector (standard)	X			
10		230 V Connector (CEE)	X			
11	M4	Shackle	X			
12	M5	Screw driver	X			
12	M6	Use of a drill		X (90%)		
13	M7	Pipe star (position and orientation)		X (95%)		
14		Pipe star (visual)	X			
15	A1	Autonomous locomotion			X (75%)	
16	A2	Autonomous manipulation			X (75%)	
17	IM1	Integrated mission				X
		Summary	11	2	3	1

From the five tasks with non-complete success (M1, M6, M7, A1, A2), two have a performance level of over 90%. Three tasks (M1 “Valve gate type”, A1 “Autonomous locomotion”, and A2 “Autonomous manipulation”) are assessed as partial success and Task IM1 “Integrated mission” failed. An analysis of the reasons for partial success and failure is done in Section 5.

In summary, about 76% of the tasks (13 of 17) were performed successfully.

Table 2 reports the operation time for each of the tasks performed at the Final Evaluation. Again, an analysis is provided in Section 5. Table 3 lists the used control interfaces for the individual tasks.

Table 2: Operation times of the tasks performed at the Final Evaluation.

Nr.	Task name	Task object	Operat. time			Perf.	Remark
			h	min	sec		
1	L1	Regular door with handle and lock	0	13	30	100	
2	L2	Step-field with debris	1	27	38	100	See Analysis 5.1
3	L3	Stair	0	10	2	100	
4	L4	Gap	0	3	26	100	
5	M1	Valve (Gate type)	0	23	30	60	One turn only in each direction See Analysis 5.2
7		Valve (lever type)	0	6	50	100	
8	M2	Fire hose	0	10	10	100	
9	M3	230V-Connector (standard)	0	6	50	100	
10		230V-Connector (CEE)	0	10	0	100	
11	M4	Shackle	0	24	35	100	
12	M5	Screw driver	0	6	21	100	
12	M6	Use of a drill	0	2	50	90	On/off switch not used
13	M7	Pipe star (pos+orient)	0	14	23	95	Pipe on top only reached from one side
14		Pipe star (visual)	0	6	9	100	
15	A1	Autonomous locomotion	0	2	50	75	Stopped with only one leg on the platform, see Analysis 5.3
16	A2	Autonomous manipulation	0	0	0	75	Drill lost balance, see Analysis 5.4
17	IM1	Integrated mission	0	0	0	0	Problem of wireless data transmission, see Analysis 5.5

Table 3: Used control interfaces for individual tasks.

Nr.	Task name	Task object	Used control interfaces
1	L1	Regular door with handle and lock	Joystick + 6D mouse
2	L2	Step-field with debris	Joystick + Semiautonomous stepping controller + 6D mouse + Keyframe editor
3	L3	Stair	Joystick + Keyframe editor
4	L4	Gap	Joystick + Keyframe editor
5	M1	Valve (Gate type)	Joystick + Semiautonomous stepping controller + Fullbody telepresence station
7		Valve (lever type)	Joystick + Semiautonomous stepping controller + Fullbody telepresence station/6D mouse
8	M2	Fire hose	Joystick + 6D mouse
9	M3	230V-Connector (standard)	Joystick + Fullbody telepresence station/6D mouse
10		230V-Connector (CEE)	Joystick + 6D mouse
11	M4	Shackle	Joystick + 6D mouse
12	M5	Screw driver	Joystick + 6D mouse
12	M6	Use of a drill	Joystick + 6D mouse
13	M7	Pipe star (pos+orient)	Joystick + 6D mouse + Keyframe editor
14		Pipe star (visual)	Joystick + 6D mouse + Keyframe editor
15	A1	Autonomous locomotion	Autonomous hybrid driving-stepping locomotion planner
16	A2	Autonomous manipulation	Autonomous bimanual manipulation controller
17	IM1	Integrated mission	-

5 Analysis

5.1 Long Operation Time for Task L2 “Step field”

Overcoming the step field took a long time since no optimal user interface was available and thus, numerous manual adjustments were required. The semi-autonomous stepping controller was applicable to the step field itself but as soon as the robot had to step on one of the wooden bars, precise manual foot adjustment and balancing by keyframe editor and 6D input device was required to position the individual feet on suitable footholds.

In addition, one of the RGB cameras mounted under the robot body lost connection. The operators used the RGB camera at the robot wrist instead. This worked sufficiently well to assess the robot state but required frequent additional adjustments to obtain the necessary field of view.

5.2 Partial Success of Task M1 “Gate type valve”

The gate type valve was operated using the exoskeleton-interface. Due to mechanical problems with the wires of the drives, the valve could only be turned by one rotation in both directions. After switching to the third-person operator interfaces (6D mouse), the task was completed.

5.3 Partial Success of Task A1 “Autonomous locomotion”

The robot started in front of a patch of gravel and successfully navigated around it to climb a flight of stairs. The robot lost balance when trying to reach the first step with the second rear foot. The reason was that some hardware components such as the battery and computing units moved to different locations but these changes were not included in the digital robot model (URDF file). Hence, the weight distribution of the real robot and the simulated robot differed and the controller which was parametrized in the simulation did not know about this difference.

5.4 Partial Success of Task A2 “Autonomous manipulation”

The robot started in front of an unknown drill tool with two handles. It successfully grasped the drill with both hands and lifted it. Due to a slight misalignment of the right-hand grasp, it failed to switch the drill on. The robot put the drill back on the table, but the drill lost balance after the robot opened its hands.

5.5 Failing Task IM1 “Integrated mission”

The root of the failure in this task is still under investigation. It is probably related to the fact that the long distance between the operator station and the robot caused a limited bandwidth for the wireless data link which resulted in dropped messages of joint references and finally resulted in jumps in those references. This caused the ankle yaw joints to accelerate strongly and damage the mechanical stop of those joints.

6 Conclusions

The Final Evaluation Camp has shown that the CENTAURO system complies with the specified functionality. About 76 % of the tasks could be performed with success.

The overall approach of the CENTAURO system has been verified. Especially the use of two arms has enlarged the functionality and enhanced the range of tasks which could be performed. An example is the plugging and unplugging of the 230 V standard connector. Without using a second hand it is impossible to solve such a task.

The hybrid wheeled-legged locomotion of the Centauro robot was a well-chosen approach for the challenging and manifold disaster-response typical locomotion tasks. The hybrid driving-stepping locomotion is more flexible than the locomotion of tank-like systems. In comparison to purely legged systems, the energy efficient and fast omnidirectional driving was superior in many cases while legged locomotion was available for more challenging situations.

The evaluation has also shown that the operator interface – including the kinematic and dynamic simulation of the robot – plays an important role for the performance of the whole disaster-response system. Hence, future developments of the ergonomics could further improve the system performance. The present human-machine-interface was adapted to the skills of an experienced software engineer. Professional rescue workers might have different capabilities – the interfaces should be usable by a wide variety of operators. A deeper examination of the operator requirements and the human-robot interface could help to further improve the capabilities of the CENTAURO system towards a powerful disaster-response system, able to perform complex locomotion and manipulation tasks in hostile environments instead of rescue workers in order to mitigate the effects of disasters.

Annex A: Evaluation Protocol

Test protocol				
Final evaluation CENTAURO				
Task-Number				
Task-Name				
Modus	Teleoperated	<input type="checkbox"/>	Autonomous	<input type="checkbox"/>
100%-criteria				
Max. trial number		Trial number		
Name of operators				
Name of PAL				
Name of referee				
Starting parameters	ok	<input type="checkbox"/>	not ok	<input type="checkbox"/>
Starting time				
End time				
Operational time				
Number of interacts	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>
			Referee	<input type="checkbox"/>
End of test	100%-criteria	<input type="checkbox"/>	Operator	<input type="checkbox"/>
			Referee	<input type="checkbox"/>
Performance level				
Remarks¹⁾				
<p>1) If not possible record on backside or separate paper</p>				
Date		Sign of referee		

Annex B: Evaluation tasks

Locomotion

Nr.	Task object	Task Description	Difficulty No of trials	Op-Mode	Equipment	Starting point	“100%”- criteria	Remarks
L1	Regular door with handle and lock 200 cm x 90 cm Hinges on right side Locked with a key No Closing mechanism 240 degree rotation needed to unlock.	Opening the door away from the robot. Unlock with specially prepared key (adapter). Use handle. Keep door open. Move through the door.	6 2 trials	teleoperated	Specially equipped key	1 m in front of the door	Door is open and robot has moved through the door	IIT makes an adaptor of the key to the Heri-hand. KHG delivers specification of key adaptor. SSSA mainly interested in the unlocking part. Switch from exoskeleton to UBO interface needed. UBO prepares
L2	Step-field Width 150 cm Length 250 cm Made of concrete blocks max. height difference: 20 cm Debris on the field: 5 wooden beams (LxBxH:100x10x10cm)	Walking over the step field	8 3 Trials	teleoperated	Concrete blocks Debris	1 m in front of the step-field	Walk completely over the step-field without falling	KHG provides debris and bricks UBO semi-autonomous stepping Go in different directions over the step-field
L3	Stair 3 steps Width 100 cm step height 20 cm, depth 30 cm landing on a platform	Walking up a stair	9 2 Trials	teleoperated	Concrete blocks	1 m in front of the stair	Walk up the stair to the platform without falling	UBO motion primitives IIT makes sure that gantry works for stairs

Nr.	Task object	Task Description	Difficulty No of trials	Op-Mode	Equipment	Starting point	“100%”- criteria	Remarks
L4	Gap Build from concrete blocks width 50 cm	Overcoming the gap	4 3 Trials	teleoperated	Concrete blocks	On one platform in frnt	On the other platform behind the gap	UBO motion primitives

Manipulation

Nr.	Task object	Task Description	Difficulty No of trials	Op-Mode	Equipment	Starting point	“100%”- criteria	Remarks
M1	Valve (gate type) valve in center position mounted on a plate fixed at a workbench 120 cm above floor level wheel orientation adjustable uneven ground in front of the valve (front and back legs not at the same level)	Open and close the valve (multiple turns of hand wheel)	5 2 Trials	teleoperated	Valve	1 m in front of the platform	Open and close the valve	Front legs elevated 20 cm relative to the back legs. Platform 100x60x20 Switch between stepping and left-hand manipulation
	Valve (lever type) lever length 10 cm see M1a	Open and close the valve (90° turn of lever)	4 2 Trials	teleoperated	Valve	1 m in front of the workbench	Open and close the valve	Same as above
M2	Fire hose Bajonett type, Fixed part mounted on a support construction in a clamp, 100 cm above the floor, orientation adjustable, Loose hose part in the gripper Use of a special tool (hook wrench) Without a seal	Connect the fire hose (push and turn 45°)	8 2 Trials	teleoperated	Fire hose Hook wrench	1m in front of the workbench Loose hose part in the left gripper, tool in the right hand	Connect the fire hose (30°)	Holes in the hose at 60° separation. Foam protection on tool by UBO
M3	230V-Connector Standard household “Schuko”-plug in one gripper. Outlet at reachable location with the second gripper and in a predefined orientation	Connect and disconnect the connector	7 2 Trials	Teleoperated	Standard 230V-connector	1m in front of the workbench Loose end easily accessible without moving legs	Connect and disconnect the household 230V-connector	No repositioning of legs should be required

Nr.	Task object	Task Description	Difficulty No of trials	Op-Mode	Equipment	Starting point	“100%”- criteria	Remarks
	230V-Connector CEE-Type with lid. Fixed part on the wall. Plug at reachable location with the second gripper and in a predefined orientation	Connect and disconnect the connector	8 2 Trials	Teleoperated	CEE 230V-connector with lid	1 m in front of the workbench Loose end easily accessible without moving legs	Connect and disconnect the 230V-CEE-connector	Same as above
M4	Shackle Closing of a shackle. Vertical ring fixed on wall M12 pin	Close a shackle	9 3 Trials	teleoperated	Shackle	1m in front of the workbench Shackle in one hand. Pin in the other hand	Metal ring hooked in the shackle Screw locked 4-5 turns	Extension of the pin may be necessary by SSSA
M5	Screw driver Wooden board (thickness 5mm) screwed in a wooden block. 1 m above the floor, orientation adjustable Board with 2 premounted screws in one hand, screw driver in the other, Torx 25 screw driver	Turn screws completely in the woodblock	8 3 Trials	teleoperated	TORX-25-screw driver Screws Woodblock	1m in front of the workbench Board in one hand and screw driver in the other Board approx. 10x50x2 cm	Screws completely turned in the wooden block	Space for robot hand fingers is required Screw in the woodblock
M6	Use of a drill Wooden block mounted on a support construction in a clamp 100 cm above the floor horizontal drill Drill diameter 8mm Use of a drill 2 handed driller with battery	Drill a hole (complete length of driller)	5 3 Trials	teleoperated	2-handed-electric driller Driller 6 Woodblock	1m in front of the workbench Drill is the robot hands A mark for where the hole should be made	Hole with complete length of driller drilled in the wooden block	Extension for 2 handed operation by UBO Hole in the woodblock 1cm from the mark

Nr.	Task object	Task Description	Difficulty No of trials	Op-Mode	Equipment	Starting point	“100%”- criteria	Remarks
M7	Pipe star Pipes arranged like a star. The star positioned 1m in front of the robot on the ground. Try to grasp the pipes with one hand. Orientation of the hand correlates to the direction of the pipe	Evaluates workspace of the robot	5 3 Trials	teleoperated	KHG-„SMF-Halle	1m in front of the pipe star	All pipes grasped with one hand	M9a and M9b can be combined All pipes grasped with the correct position
	Pipe star The star arranged 1m in front of the robot on the bottom.. In the pipes in a certain depth: Landolt rings: Try to look in each pipe and solve the eye test	Evaluates vision space of the robot	5	teleoperated	KHG-„SMF-Halle	1m in front of the pipe star	All Landolt rings detected correctly	See above All openings in the Landolt rings seen

Supervised Autonomous Tasks

Task A1: Autonomous locomotion

Scenario

The robot stands in front of multiple fields of gravel/grass which have to be traversed. There are some difficulties:

- In addition, some obstacles which cannot be traversed, block certain areas
- The desired goal pose is located on an elevated platform which can be reached by climbing a stair with 2 steps

100%-criteria

Terrain classification detects the gravel/grass/obstacles/stairs and generates a terrain class map:

- A height map is generated from registered laser scanner point clouds
- Terrain classes and height information are merged to a cost map
- The operator inputs the desired goal pose (x,y,orientation) through a VEROSIM interface
- The planner plans multiple paths with different costs for gravel/grass and outputs two solutions:
 - a) low costs to traverse gravel/grass
 - b) high costs to traverse gravel/grass
- The operator chooses option b) which is then executed by the robot

> Difficulty/Number of trials

- 8/3

Task A2: Autonomous manipulation**Scenario**

The robot stands in front of a table and should autonomously grasp a tool.

- The surface of the table of standard height (~75 cm) is in the workspace of the robot.
- There is a 2-handed-driller located on the table. The tool is in such position that it is possible to grasp it directly (maybe with one hand only) without any additional manipulations.
- The tool has to be held with both hands in order to be used properly.
- There is an obstacle on the table, obstructing an easy direct way of approaching a pre-grasp pose.
- The task is to successfully pick up the tool, lift it, switch it on and off, place it back.

100%-criteria

- The tool is recognized and its pose is estimated.
- Necessary grasping poses are generated using non-rigid registration.
- Initial grasping trajectories are generated using keyframe interpolations
- The trajectories are optimized under multiple objectives.
- Trajectory is executed, followed by the grasping, lifting, switching on/off and placing the tool back onto the table.
- Note, that the tool does not have to be grasped with two hands directly from the table. It is possible to first lift it up with one arm and involve the other arm afterwards.

Difficulty/Number of trials

- 8/3

Annex C Protocols

By
date

Test protocol				Final evaluation CENTAURO		L1		
Task-Number	0204	= L1						
Task-Name	Regular door -outward							
Modus	Teleoperated	<input checked="" type="checkbox"/>	Autonomous	<input type="checkbox"/>	Simulation	<input type="checkbox"/>		
100%-criteria	Unlock door, open, drive through,							
Max. trial number		Trial number	1					
Name of operators	Max, Chris							
Name of PAL								
Name of referee	Kerl							
Starting parameters	ok	<input checked="" type="checkbox"/>	not ok	<input type="checkbox"/>				
Starting time	19.25							
End time								
Operational time	13:30							
Number of interacts	Operator		PAL		Referee			
End of test	100%-criteria	<input checked="" type="checkbox"/>	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>	Referee	<input type="checkbox"/>
Performance level[%]	100%							
Remarks ¹⁾	No crane On battery							
1) If not possible record on backside or separate paper								
Date	11/10-18		Sign of referee					

Test protocol
Final evaluation CENTAURO

L2

Task-Number	L2		
Task-Name	Step-field		
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>
100%-criteria			
Max. trial number		Trial number	4

Name of operators	
Name of PAL	
Name of referee	Karl

Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>
----------------------------	--	---------------------------------

Starting time	15:40
End time	
Operational time	1:26:38

Number of interacts	Operator		PAL		Referee	
----------------------------	-----------------	--	------------	--	----------------	--

End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/>	Referee <input type="checkbox"/>
--------------------	---	-----------------------------------	------------------------------	----------------------------------

Performance level[%]	100%
-----------------------------	------

Remarks¹⁾
 Gauntlet for safety meas.


1) If not possible record on backside or separate paper

Date	10/16-18	Sign of referee	
-------------	----------	------------------------	--

Chris

Test protocol				Final evaluation CENTAURO		L3		
Task-Number	L3							
Task-Name	Stair - up							
Modus	Teleoperated	<input checked="" type="checkbox"/>	Autonomous	<input type="checkbox"/>	Simulation	<input type="checkbox"/>		
100%-criteria	Climb stairs and stop at top							
Max. trial number			Trial number	1				
Name of operators	Max, Chris.							
Name of PAL	Michael							
Name of referee	Karl							
Starting parameters	ok	<input checked="" type="checkbox"/>	not ok	<input type="checkbox"/>				
Starting time	18:40							
End time								
Operational time	10:02							
Number of interacts	Operator		PAL		Referee			
End of test	100%-criteria	<input checked="" type="checkbox"/>	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>	Referee	<input type="checkbox"/>
Performance level[%]	100%							
Remarks ¹⁾	Only 3 steps in staircase							
1) If not possible record on backside or separate paper								
Date	11/16-18		Sign of referee	[Signature]				

Test protocol			
Final evaluation CENTAURO			
L4			
Task-Number	L4		
Task-Name	Gap		
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>
100%-criteria	Walk over the gap - no falling		
Max. trial number		Trial number	1
Name of operators	Christian, Max		
Name of PAL			
Name of referee	Karl		
Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>	
Starting time	18:46		
End time	+		
Operational time	3:26		
Number of interacts	Operator	PAL	Referee
End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/> Referee <input type="checkbox"/>
Performance level[%]	100%		
Remarks¹⁾ No gantry + Battery used (without cable) Teleoperated w/o using simulator without			
<small>1) If not possible record on backside or separate paper</small>			
Date	10/10-18	Sign of referee	<i>[Signature]</i>

Test protocol Final evaluation CENTAURO			
Task-Number	C2A 7 NA		
Task-Name	Valve-gate		
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>
100%-criteria	Open + close gate-valve		
Max. trial number		Trial number	2
Name of operators	Nasornin		
Name of PAL	Narvab		
Name of referee			
Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>	
Starting time	16.10		
End time			
Operational time	23:30		
Number of interacts	Operator	PAL	Referee
End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/> Referee <input type="checkbox"/>
Performance level[%]	60%		
Remarks ¹⁾	~1 turn each direction		
Date	11/10-19	Sign of referee	

1) If not possible record on backside or separate paper

At
value
low

Test protocol				
Final evaluation CENTAURO				
Task-Number	C26 + PA			
Task-Name	Valve - lever type			
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>	
100%-criteria	Open + Close lever (~90°)			
Max. trial number		Trial number	1	
Name of operators	Massimiliano (exoskel.), Chris., Max, (Bonn)			
Name of PAL	Navvab			
Name of referee	Karl			
Starting parameters	ok <input checked="" type="checkbox"/>	starting w/ legs not ok <input type="checkbox"/>	on platform	
Starting time	16:39			
End time				
Operational time	6:50			
Number of interacts	Operator	PAL	Referee	
End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/>	Referee <input type="checkbox"/>
Performance level[%]	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> 70% 100% / 6 Bonn 100% </div>			
Remarks ¹⁾	<p>30° down by exoskeleton, broken afterwards → Bonn continues task (operates using wrist)</p> <p>* SARA starts the winter after 70% of active exoskel failed, USO finished the task</p>			
1) If not possible record on backside or separate paper				
Date	11/10 - 18	Sign of referee	Karl	



of
Fire hose

Test protocol
Final evaluation CENTAURO

M2

Task-Number	M1 1	
Task-Name	Fire hose - w/o seal	
Modus	Teleoperated <input checked="" type="checkbox"/> Autonomous <input type="checkbox"/> Simulation <input type="checkbox"/>	
100%-criteria	Connect and fasten hose using tool	
Max. trial number	Trial number	3

Name of operators	Max, Christian
Name of PAL	Tobias
Name of referee	Karl

Starting parameters	ok <input checked="" type="checkbox"/> not ok <input type="checkbox"/>
----------------------------	--

Starting time	8.50
End time	
Operational time	10:10

Number of interacts	Operator	PAL	Referee
----------------------------	-----------------	------------	----------------

End of test	100%-criteria <input checked="" type="checkbox"/> Operator <input type="checkbox"/> PAL <input type="checkbox"/> Referee <input type="checkbox"/>
--------------------	---



Performance level[%]	100%
-----------------------------	------

Remarks¹⁾
w/ crane


1) If not possible record on backside or separate paper

Date	12/10 - 13	Sign of referee	
-------------	------------	------------------------	---

27.02

Test protocol			
Final evaluation CENTAURO			
Task-Number	M3a		
Task-Name	230V-connector - lose outlet		
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>
100%-criteria	Plug the contacts together		
Max. trial number		Trial number	1
Name of operators	Max, Chris		
Name of PAL	Michael		
Name of referee	Karl		
Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>	
Starting time	17:08		
End time			
Operational time	6:50		
Number of interacts	Operator	PAL	Referee
End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/> Referee <input type="checkbox"/>
Performance level[%]	100%		
Remarks ¹⁾	<p>No crane, plug freehanging from ceiling, no known orientation</p> <p>Driving required to reach</p> 		
1) If not possible record on backside or separate paper			
Date	11/10-18	Sign of referee	

220
CW

Test protocol				Final evaluation CENTAURO		h3		
Task-Number	M216							
Task-Name	230V-Connector		CEE-Type					
Modus	Teleoperated	<input checked="" type="checkbox"/>	Autonomous	<input type="checkbox"/>	Simulation	<input type="checkbox"/>		
100%-criteria	Plug-in socketlight 4							
Max. trial number			Trial number	1				
Name of operators	Max, Chris							
Name of PAL	Tobias							
Name of referee	Karl							
Starting parameters	ok	<input checked="" type="checkbox"/>	not ok	<input type="checkbox"/>				
Starting time	18:08							
End time								
Operational time	10:00							
Number of interacts	Operator		PAL		Referee			
End of test	100%-criteria	<input checked="" type="checkbox"/>	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>	Referee	<input type="checkbox"/>
Performance level[%]	100%							
Remarks ¹⁾	w/ Crane							
1) If not possible record on backside or separate paper								
Date	11/10-18		Sign of referee					

Scheid

Test protocol Final evaluation CENTAURO		M4
--	--	----

Task-Number	M4
--------------------	----

Task-Name	Shackle
------------------	---------

Modus	Teleoperated <input checked="" type="checkbox"/> Autonomous <input type="checkbox"/> Simulation <input type="checkbox"/>
--------------	--

100%-criteria	Close around ring + >6 turns
----------------------	------------------------------

Max. trial number		Trial number	1
--------------------------	--	---------------------	---

Name of operators	Christian, Max
--------------------------	----------------

Name of PAL	Michael
--------------------	---------

Name of referee	Karl
------------------------	------

Starting parameters	ok <input type="checkbox"/> not ok <input type="checkbox"/>
----------------------------	---

Starting time	14:50
----------------------	-------

End time	
-----------------	--

Operational time	24:35
-------------------------	-------

Number of interacts	Operator	PAL	Referee
----------------------------	-----------------	------------	----------------

End of test	100%-criteria <input checked="" type="checkbox"/> Operator <input type="checkbox"/> PAL <input type="checkbox"/> Referee <input type="checkbox"/>
--------------------	---

Performance level[%]	100%
-----------------------------	------

Remarks¹⁾			
-----------------------------	--	--	--

No crane

Shackle with special grip adapter


1) If not possible record on backside or separate paper

Date	11/10-13	Sign of referee	
-------------	----------	------------------------	--

Simon de
&

Test protocol				75	
Final evaluation CENTAURO					
Task-Number	M5				
Task-Name	Screw-driver				
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>		
100%-criteria	Score				
Max. trial number		Trial number	1		
Name of operators	Max, Christian				
Name of PAL	Michael				
Name of referee	Karl				
Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>			
Starting time	13.56				
End time					
Operational time	6:21				
Number of interacts	Operator	PAL	Referee		
End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/>	Referee <input type="checkbox"/>	
Performance level[%]	100%				
Remarks ¹⁾	w/o Crane two screws fixed				
1) If not possible record on backside or separate paper					
Date			Sign of referee		

for all

Test protocol						76		
Final evaluation CENTAURO								
Task-Number	M6							
Task-Name	Use of drill							
Modus	Teleoperated	<input checked="" type="checkbox"/>	Autonomous	<input type="checkbox"/>	Simulation	<input type="checkbox"/>		
100%-criteria	Hole full-length at mark							
Max. trial number		Trial number	2					
Name of operators	Max, Christian							
Name of PAL	Michael							
Name of referee	Karl							
Starting parameters	ok	<input checked="" type="checkbox"/>	not ok	<input type="checkbox"/>				
Starting time	10:54							
End time								
Operational time	1:55							
Number of interacts	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>	Referee	<input type="checkbox"/>		
End of test	100%-criteria	<input checked="" type="checkbox"/>	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>	Referee	<input type="checkbox"/>
Performance level[%]	90% [±] _±							
Remarks ¹⁾	<p>Hole #2 w/ cable drill cont. drilling &</p> <p>Slightly off mark (see image) [±] _±</p>							
1) If not possible record on backside or separate paper								
Date	10/10-13		Sign of referee					

Test protocol
Final evaluation CENTAURO

17

Task-Number	<i>C7a</i>	<i>17</i>	
--------------------	------------	-----------	--

Task-Name	<i>Pipe star - grasp</i>		
------------------	--------------------------	--	--

Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>
--------------	--	-------------------------------------	-------------------------------------

100%-criteria	<i>Grasp each pipe in the direction of it</i>		
----------------------	---	--	--

Max. trial number		Trial number	<i>7</i>
--------------------------	--	---------------------	----------

Name of operators	<i>Christian, Max</i>		
--------------------------	-----------------------	--	--

Name of PAL	<i>Michael</i>		
--------------------	----------------	--	--

Name of referee	<i>Karl</i>		
------------------------	-------------	--	--

Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>	
----------------------------	--	---------------------------------	--

Starting time	<i>17,52</i>		
----------------------	--------------	--	--

End time			
-----------------	--	--	--

Operational time	<i>14:23</i>		
-------------------------	--------------	--	--


Number of interacts	Operator	PAL	Referee
----------------------------	-----------------	------------	----------------

--	--	--	--

End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/>	Referee <input type="checkbox"/>
--------------------	---	-----------------------------------	------------------------------	----------------------------------

Performance level[%]	<i>95%</i>		
-----------------------------	------------	--	--

Remarks¹⁾			
-----------------------------	--	--	--

Pipes:
111 sides OK
1 top - Just from side 
No gauntry

1) If not possible record on backside or separate paper

Date	<i>10/10-18</i>	Sign of referee	
-------------	-----------------	------------------------	---

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--

--	--	--	--


--	--	--	--

--	--	--	--


--	--	--	--

--	--	--	--

7
m
sh

Test protocol				77
Final evaluation CENTAURO				
Task-Number	Star 7-17			
Task-Name	Pipe star - Visual			
Modus	Teleoperated <input checked="" type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>	
100%-criteria	Look into pipe and see pattern			
Max. trial number		Trial number	1	
Name of operators	Max, Christian			
Name of PAL	Michael			
Name of referee	Karl			
Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>		
Starting time	17:40			
End time				
Operational time	6:09			
Number of interacts	Operator	PAL	Referee	
End of test	100%-criteria <input checked="" type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/> Referee <input type="checkbox"/>	
Performance level[%]	100%			
Remarks ¹⁾	No gountry sides OK top OK			
1) If not possible record on backside or separate paper				
Date	10/10-13	Sign of referee		

Test protocol			
Final evaluation CENTAURO			
Task-Number	A2		
Task-Name	Locomotion		
Modus	Teleoperated <input type="checkbox"/>	Autonomous <input checked="" type="checkbox"/>	Simulation <input type="checkbox"/>
100%-criteria	Plan multiple paths - execute safe safely		
Max. trial number		Trial number	1
Name of operators	Max, Tobias		
Name of PAL	Michael		
Name of referee	Karl		
Starting parameters	ok <input checked="" type="checkbox"/>	not ok <input type="checkbox"/>	
Starting time	12.12		
End time			
Operational time	3:17		
Number of interacts	Operator	PAL	Referee
End of test	100%-criteria <input type="checkbox"/>	Operator <input checked="" type="checkbox"/>	PAL <input type="checkbox"/> Referee <input type="checkbox"/>
Performance level[%]	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> 75% 75% 80% 80% </div>		
Remarks ¹⁾	<p>Time excludes planning + mapping time</p> <p>Gauntry for safety</p> <p>Stopped with only front leg on platform (localization lost)</p>		
1) If not possible record on backside or separate paper			
Date	11/10-13	Sign of referee	<i>Karl</i>

Test protocol				Final evaluation CENTAURO		P2		
Task-Number	A2							
Task-Name	Grouping / manipulation							
Modus	Teleoperated	<input type="checkbox"/>	Autonomous	<input checked="" type="checkbox"/>	Simulation	<input type="checkbox"/>		
100%-criteria	detect, grasp, pickup, use, put down							
Max. trial number			Trial number	1				
Name of operators	Diego, Max, Dmytro							
Name of PAL	Michael							
Name of referee	Karl							
Starting parameters	ok	<input checked="" type="checkbox"/>	not ok	<input type="checkbox"/>				
Starting time	12.25							
End time								
Operational time	0:55							
Number of interacts	Operator		PAL		Referee			
End of test	100%-criteria	<input type="checkbox"/>	Operator	<input type="checkbox"/>	PAL	<input type="checkbox"/>	Referee	<input type="checkbox"/>
Performance level[%]	-							
Remarks ¹⁾	<p>w/ crane Failed to start drill Drill fell after putting it down</p>							
1) If not possible record on backside or separate paper								
Date	12/10-18		Sign of referee					

IMA

Test protocol			
Final evaluation CENTAURO			
Task-Number	1071		
Task-Name	Integrated mission		
Modus	Teleoperated <input type="checkbox"/>	Autonomous <input type="checkbox"/>	Simulation <input type="checkbox"/>
100%-criteria			
Max. trial number		Trial number	
Name of operators			
Name of PAL			
Name of referee			
Starting parameters	ok <input type="checkbox"/>	not ok	<input type="checkbox"/>
Starting time			
End time			
Operational time			
Number of interacts	Operator	PAL	Referee
End of test	100%-criteria <input type="checkbox"/>	Operator <input type="checkbox"/>	PAL <input type="checkbox"/> Referee <input type="checkbox"/>
Performance level[%]			
Remarks ¹⁾			
not started due to problems with wireless link			
1) If not possible record on backside or separate paper			
Date		Sign of referee	